




CSC BEARING GROUP limited

200 mm x 310 mm x 109 mm SKF 24040 CC/W33 Spherical roller bearing

Bearing No. 24040 CC/W33



24040 CC/W33 Bearing 2D drawings and 3D CAD models

| | |
|---|----------------|
| Size | 310x200x109 mm |
| Bore Diameter | 310 mm |
| Outer Diameter | 200 mm |
| Width | 109 mm |
| d | 200 mm |
| D | 310 mm |
| B | 109 mm |
| d ₂ | 223 mm |
| D ₁ | 268 mm |
| b | 11.1 mm |
| K | 6 mm |
| r _{1,2} - min. | 2.1 mm |
| d _a - min. | 211 mm |
| D _a - max. | 299 mm |
| r _a - max. | 2 mm |
| Basic dynamic load rating - C | 1353 kN |
| Basic static load rating - C ₀ | 2120 kN |
| Fatigue load limit - P _u | 186 kN |
| Reference speed | 1300 r/min |
| Limiting speed | 1900 r/min |
| Calculation factor - e | 0.33 |
| Calculation factor - Y ₁ | 2 |
| Calculation factor - Y ₂ | 3 |
| Calculation factor - Y ₀ | 2 |



CSC BEARING GROUP limited

| | |
|---------------------------|---|
| Category | Spherical Roller Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 31.718 |
| EAN | 7316570852509 |
| Product Group | B04311 |
| Internal Clearance | C0-Medium |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Straight |
| Cage Material | Steel |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |
| Withdrawal Sleeve | Not Applicable |
| Withdrawal Nut | Not Applicable |
| Inch - Metric | Metric |
| Long Description | 200MM Straight Bore; 310MM Outside Diameter; 109MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable |
| Category | Spherical Roller Bearing |
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |
| Noun | Bearing |
| Keyword String | Spherical |
| Manufacturer URL | http://www.skf.com |
| Weight / LBS | 69.864 |
| Outside Diameter | 12.205 Inch 310 Millimeter |
| | |



CSC BEARING GROUP limited

| | |
|--------------------------------|---|
| Width | 4.291 Inch 109 Millimeter |
| Bore | 7.874 Inch 200 Millimeter |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| bore diameter: | 200 mm |
| maximum rpm: | 1900 RPM |
| outside diameter: | 310 mm |
| operating temperature range: | Maximum of +390 ° F |
| overall width: | 109 mm |
| cage material: | Steel |
| bore type: | Straight |
| bearing material: | Steel |
| outer ring type: | Not Split |
| cage type: | Inner Ring Guided |
| internal clearance: | C0 |
| precision rating: | Not Rated |
| closure type: | Open |
| finish/coating: | Uncoated |
| lubrication hole type: | Lubrication Groove & Hole |
| outer ring width: | 109 mm |
| dynamic load capacity: | 1290 kN |
| fillet radius: | 2 mm |
| static load capacity: | 2120 kN |
| series: | 240 |
| d_2 | 223 mm |
| D_1 | 268 mm |
| $r_{1,2}$ min. | 2.1 mm |
| d_a min. | 211 mm |
| D_a max. | 299 mm |
| r_a max. | 2 mm |
| Basic dynamic load rating C | 1353 kN |
| Basic static load rating C_0 | 2120 kN |



CSC BEARING GROUP limited

| | |
|--------------------------|--------|
| Fatigue load limit P_u | 186 kN |
| Calculation factor e | 0.33 |
| Calculation factor Y_1 | 2 |
| Calculation factor Y_2 | 3 |
| Calculation factor Y_0 | 2 |
| Mass bearing | 31 kg |